

aquamax KF Online

Online water determination in petroleum products

Product description

The gas extraction is the ideal method to detect moisture in oil samples and viscous substances. The Aquamax KF Online is suitable for the continuous analysis of water in oil samples.

Trace amounts of water can be measured with the special heating chamber for oils. The sample has no contact with the reagent. Therefore the consumption of reagent is low and the detection sensitivity is high.

The oil sample is transferred automatically from sampling point of running process by using the pump module. The sample is injected into heating oven without any contamination. Oil sample volumes can be used in a range from 0.01 up to 20 mL depending on water content.

The sample can be heated out with temperature program or isothermal heating. The measurement is carried out in the measuring cell with titration method according to Karl Fischer. After analysis, the used oil sample flows out through a valve or returns to the running process.

With closed-loop carrier gas circulation, any additional gas drying is no longer necessary: the carrier gas is continually titrated to dryness within the closed loop. The total dryness of the gas enhances the moisture desorption from the sample. Moreover, sensitive samples can be heated out very gently. Degradations and side reactions are eliminated.




Aquamax KF Online for online water determination

Applications


- Transformer oil regeneration
- Oil treatment plant
- Refineries
- Pipelines
- Crude petroleum monitoring

Advantages

- Closed-loop carrier gas circulation
- No contact of sample with the reagent
- Low consumption of reagent
- Water determination down to 0.1 ppm
- Absolute measurement without calibration or titer determination
- No sample preparation
- For sample amounts from 0.01 up to 20 mL
- Short measuring time
- No blank value, low drift
- Freely selectable heating temperature
- Return of oil sample into system possible
- Applicable for monitoring over long period



Closed-loop carrier gas circulation




Measurement of mineral oil

Features and Results


The sample ways are coupled directly with monitoring process. Thereby the oil sample is transferred into the Aquamax KF Online without any contamination. The sample transfer can be adjusted to an automatic procedure.

The control system is adjustable for various parameters:

- Delivery rate of dosing pump
- Rinsing steps
- Emptying of oil chamber



Principle of automatic sampling and circulation



Preparation of measurement procedure


Date	File name	Start time	Sample name	Sample amount	Result	Carried out by
19.11.2015	2015111900	13:36:35	Oil 1	2.000 ml	26.6 ppm
19.11.2015	2015111901	13:40:44	Oil 1	2.000 ml	25.4 ppm
19.11.2015	2015111902	13:44:16	Oil 1	2.000 ml	25.7 ppm

Evaluation of sub measurements:	
Statistics	Arithmetical mean: 25.9 ppm
	Standard deviation: 0.6 ppm
	Rel. standard deviation: 2.51 %

Result overview

Technical specifications

Sample administration:	Automatically with high resolving ceramic dosing pump
Sample amount:	0.01 ... 20 mL
Heating temperature:	35 ... 150 °C
Measuring range:	> 0.1 ppm
Type of result:	µg, µg/L, mg/L, mg/kg, ppm, %, by using the formula generator
Power supply:	230 V/50 Hz; 115 V/60 Hz
Dimensions :	Approx. 600 x 720 x 370 mm (W x H x D)
Weight:	Approx. 53 kg



Drying process of oil treatment plant

ECH Elektrochemie Halle GmbH

Otto-Eißfeldt-Str. 8
D-06120 Halle (Saale)
Germany

Tel.: +49 (0) 345 279570-0
Fax: +49 (0) 345 279570-99

Email: info@echscientific.com • www.ech.de • www.aquamaxkf.com

ECH Scientific Limited

Building 69, Wrest Park, Silsoe
Bedfordshire, MK45 4HS
United Kingdom

Tel.: +44 (0) 1525 404747
Fax: +44 (0) 1525 404848



part of ECH Elektrochemie Halle
Global Sales Division

230001

the ECH advantage

in-lab | mobile | on-line | process